

PRODUCT DATA SHEET**BNO Power (D) 15W-40, API CF****Product Description:**

BNO Power (D) is specially formulated for Diesel Generator Engines. It is a multi-grade product formulated with highly refined base oils with recommended additive package which meets the requirements of API CF performance level. It is also suitable for super high performance diesel and passenger car applications.

Applications and benefits:

- Diesel Generator applications
- Desired alkaline reserves
- Prevents deposits and sludge formation
- Retains desired fluidity and viscosities at low and high temperatures.

Typical Characteristics:

Test Description	Typical Results	Method
SAE Viscosity Grade	15W-40	SAE J300
ASTM Color	3.9	ASTM D1500
Kinematic Viscosity at 40 ⁰ C, cSt	116.3	ASTM D7042
Kinematic Viscosity at 100 ⁰ C, cSt	15.1	ASTM D7042
Viscosity Index	133.0	ASTM D7042
Density at 15 ⁰ C, g/cm ³	0.8751	ASTM D7042
Pour Point, ⁰ C	Max. -24	ASTM D97
COC Flash Point, ⁰ C	Min. 210	ASTM D92
Sulphated Ash, wt%	1.3	ASTM D874
TBN, mg KOH/g	11.0	ASTM D2896

Performance Standards: API CF**Health, Safety and Environment:**

Based on available data collected from MSDS of ingredients used in the product, this product is not health hazardous. However, proper precautions should be taken to avoid long-term skin contact, exposure or accidental effect. Since it is a non-biodegradable product the used or waste oil should be recycled or disposed off in conformity to local disposal regulations to avoid environmental pollution.

(The information and figures given here are typical of current one which conforms to specifications, minor variations which do not affect product performance may occur during manufacturing.)